

DR-CASTER®



010BN 系列 150~400kgs

010 支架

- ▶ 雙層滾珠軸承轉動。
- ▶ 底板孔距符合 ISO 標準。
- ▶ 穩固中心柱。
- ▶ 金屬件鍍鋅處理。

高彈性橡膠尼龍芯輪

BN 黑色橡膠輪 / GN 灰色橡膠輪 / LN 藍色橡膠輪

- ▶ 高品質彈性橡膠,表面硬度邵氏 65°A,經過硫化加工及化學黏合在尼龍芯上。
- ▶ 載重力強,滾動阻力小,耐磨,防止跳動,保護運載物品及無噪音使用。
- ▶ 使用溫度: -30°C + 80°C。
- ▶ 最高使用速度 4 公里/小時。
- ▶ 符合歐盟多環芳香烴指令 2005/69/EC (PAH)。



MM	MM	MM		MM	MM	MM	MM	MM	KGS		
80	35	12	≡	105 x 85	82 x 62/78 x 58	9	105	38	150	010BN080PF	011BN080PF
80	35	12	≡	105 x 85	82 x 62/78 x 58	9	105	38	150	010BN080RF	011BN080RF
80	35	8	≡	105 x 85	82 x 62/78 x 58	9	105	38	150	010BN080BD	011BN080BD
100	36	12	≡	105 x 85	82 x 62/78 x 58	9	128	38	150	010BN100PF	011BN100PF
100	36	12	≡	105 x 85	82 x 62/78 x 58	9	128	38	150	010BN100RF	011BN100RF
100	36	8	≡	105 x 85	82 x 62/78 x 58	9	128	38	150	010BN100BD	011BN100BD
125	36	15	≡	105 x 85	82 x 62/78 x 58	9	156	41	150	010BN125PG	011BN125PG
125	36	8	≡	105 x 85	82 x 62/78 x 58	9	156	41	150	010BN125RF	011BN125RF
125	36	15	≡	105 x 85	82 x 62/78 x 58	9	156	41	150	010BN125RG	011BN125RG
125	36	10	≡	105 x 85	82 x 62/78 x 58	9	156	41	150	010BN125BE	011BN125BE
160	40	20	≡	140 x 110	110 x 85/100 x 75	11	195	60	300	010BN161RH	011BN161RH
160	40	15	≡	140 x 110	110 x 85/100 x 75	11	195	60	300	010BN161DG	011BN161DG
160	50	20	≡	140 x 110	110 x 85/100 x 75	11	195	60	400	010BN160RH	011BN160RH
160	50	20	≡	140 x 110	110 x 85/100 x 75	11	195	60	400	010BN160DH	011BN160DH
200	40	20	≡	140 x 110	110 x 85/100 x 75	11	235	67	350	010BN201RH	011BN201RH
200	40	15	≡	140 x 110	110 x 85/100 x 75	11	235	67	350	010BN201DG	011BN201DG
200	50	20	≡	140 x 110	110 x 85/100 x 75	11	235	67	400	010BN200RH	011BN200RH
200	50	20	≡	140 x 110	110 x 85/100 x 75	11	235	67	400	010BN200DH	011BN200DH



灰色彈性橡膠
010GNXXXX



全刹後制
010BNXXXX-Q



導電輪
010BNXXXX-C



全孔固定
010BNXXXX-B
ø12.3mm - B2
ø12.8mm - B3



藍色彈性橡膠
010LNXXXX



絲桿固定
010BNXXXX-T
M14 x 35mm - T27
M20 x 50mm - T29



插柱桿固定
010BNXXXX-R
ø20 x 50mm - R1
ø27 x 60mm - R3